



SAFETY DATA SHEET – RAPP-IT PIPE REPAIR BANDAGE

Infosafe No™ LPXZ9

Version No. 2.0

Issue Date: 27/10/2020



ISSUED by PIPE REPAIR INTERNATIONAL

PAGE: 1 OF 6

1. IDENTIFICATION

GHS Product Identifier	RAPP-IT PIPE REPAIR BANDAGE
Company Name	PIPE REPAIR INTERNATIONAL
Address	12/14 Argyle Street, Albion, Queensland 4010 Australia
Telephone/Fax Number	Tel: +61 7 3262 3755 Fax: +61 7 3262 3255
Emergency Phone Number	INFOTRAC 24/7 Emergency response contact phone numbers 1-800-535-5053 (free call from USA and Canada) 1-352-323-3500 (outside USA and Canada) 01-800-681-1530 (Mexico - local charges apply)
Recommended use of the chemical and restrictions on use	Used for temporary emergency pipe repair for all pipes.
Manufacturer Information	MARINE & INDUSTRIAL MARKETING 12/14 Argyle Street, Albion, Queensland 4010 Australia

2. HAZARD IDENTIFICATION

GHS classification of the substance/mixture	This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200). Not classified as Dangerous Goods by the criteria of the Department of Transport (DOT), International Air Transport Association (IATA) and International Maritime Dangerous Goods Code (IMDG). Skin Corrosion/Irritation: Category 2 Eye Damage/Irritation: Category 2 Sensitization - Respiratory: Category 1 Sensitization - Skin: Category 1 Carcinogenicity: Category 2 STOT Single Exposure: Category 3 (respiratory tract irritation) STOT Repeated Exposure: Category 2
Signal Word(s)	DANGER
Hazard Statement(s)	Causes skin irritation. Causes serious eye irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction. Suspected of causing cancer. May cause respiratory irritation. May cause damage to organs through prolonged or repeated exposure.
Pictogram(s)	Health hazard, Exclamation mark  
Precautionary Statement – Prevention	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapors/spray. Wash contaminated skin thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. In case of inadequate ventilation wear respiratory protection.
Precautionary Statement – Response	Get medical advice/attention if you feel unwell. IF exposed or concerned: Get medical advice/attention. If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
Precautionary Statement – Disposal	Dispose of contents/container to an approved waste disposal plant.
Other Information	HMIS rating: Health Hazards: 2* Flammability: 1 Physical hazard: 0 Personal Protective Equipment: X

SAFETY DATA SHEET – RAPP-IT PIPE REPAIR BANDAGE

Infosafe No™ LPXZ9

Version No. 2.0

Issue Date: 27/10/2020

ISSUED by PIPE REPAIR INTERNATIONAL

PAGE: 2 OF 6

3. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients	Name	CAS	EINECS	Proportion
	Polyurethane Prepolymer	Proprietary		40-<70 %
	Fiberglass	65997-17-3	266-046-0	30-60 %
	Diphenylmethane 4,4'- diisocyanate	101-68-8	202-966-0	1-<10 %
	Petroleum distillates, hydrotreated heavy paraffinic	64742-54-7	265-157-1	1-<3 %
	White mineral oil, petroleum	8042-47-5		1-<3 %
	Silicon dioxide, amorphous	68611-44-9	271-893-4	0.1-<1 %
	Ingredients determined not to be hazardous			Balance
Other Information	Polyurethane prepolymer contains Isocyanate-terminated and Polyol. DMSO extractible compounds according to IP 346: < 3%.			

4. FIRST AID MEASURES

Inhalation	If inhaled, remove affected person from contaminated area. Apply artificial respiration if not breathing. Seek medical attention.
Ingestion	Do not induce vomiting. Wash out mouth thoroughly with water. Seek immediate medical attention.
Skin	Remove all contaminated clothing immediately. Wash affected area thoroughly with soap and water. Wash contaminated clothing before reuse or discard. Seek medical attention.
Eye contact	If in eyes, hold eyelids apart and flush the eyes continuously with running water. Remove contact lenses. Continue flushing for several minutes until all contaminants are washed out completely. Seek medical attention.
First Aid Facilities	Eyewash, safety shower and normal washroom facilities.
Advice to Doctor	Treat symptomatically.
Other Information	For advice in an emergency, contact a Poisons Information Centre or a doctor at once.

5. FIRE FIGHTING MEASURES

Suitable Extinguishing Media	Dry chemical, carbon dioxide, regular foam extinguishing agent, spray.
Unsuitable Extinguishing Media	Avoid use of water jet for extinguishing.
Hazards from Combustion Products	Under fire conditions this product may emit toxic and/or irritating fumes, smoke and gases including carbon monoxide, carbon dioxide and oxides of nitrogen.
Specific Hazards arising from the Chemical	Combustible solid. This product will burn if exposed to fire.
Decomposition Temp.	Not available.
Precautions in connection with Fire	Fire fighters should wear Self-Contained Breathing Apparatus (SCBA) operated in positive pressure mode and full protective clothing to prevent exposure to vapors or fumes. Water spray may be used to cool down heat-exposed containers. Fight fire from safe location. This product should be prevented from entering drains and watercourses.
Other Information	NFPA rating: Health Hazards: 2 Flammability: 1 Instability: 0

6. ACCIDENTAL RELEASE MEASURES

Emergency Procedures	Remove all sources of ignition. Increase ventilation. Evacuate all unprotected personnel. Do not breathe dust. Wear respiratory protection and full protective clothing to minimise exposure. Sweep up material avoiding dust generation - dampen spilled material with water if suitable to avoid airborne dust, OR where possible use dustless methods such as vacuum to collect the material; then transfer material in to suitable vapor tight labelled containers for subsequent recycling or disposal. Dispose of waste according to applicable local and national regulations. If contamination of sewers or waterways occurs inform the local water and waste management authorities in accordance with local regulations.
----------------------	--

7. HANDLING AND STORAGE

Precautions for Safe Handling	Avoid inhalation of dust, and skin or eye contact. Use only in a well ventilated area. Avoid inhalation of dust generated when removing the product from pipes, and skin or eye contact. Use disposable gloves. Product will adhere on contact with skin or clothing, if product adheres to skin remove as soon as possible with acetone or alcohol. Prevent the build up of dust in the work atmosphere. Establish good housekeeping practices. Maintain high standards of personal hygiene i.e. washing hands prior to eating, drinking, smoking or using toilet facilities. Avoid exposure. Do not handle until all safety precautions have been read and understood. Do not use warm or hot water. Bandage may generate heat during application.
Conditions for Safe Storage including any Incompatibilities	Store in a well ventilated area away from heat and sources of ignition, out of direct sunlight and moisture. Take precautions against static electricity discharges. Use proper grounding procedures. Store away from incompatible materials such as materials that support combustion (oxidizing materials). Store in suitable, labelled containers. Inspect periodically for deficiencies such as damage or leaks. Have appropriate fire extinguishers available in and near the storage area. Ensure that storage conditions comply with applicable local and national regulations.

SAFETY DATA SHEET – RAPP-IT PIPE REPAIR BANDAGE

Infosafe No™ LPXZ9

Version No. 2.0

Issue Date: 27/10/2020

ISSUED by PIPE REPAIR INTERNATIONAL

PAGE: 3 OF 6

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupation Exposure Limit Values	Substance	Regulations	Exposure Duration	Exposure Limit	Units	Notes
	Continuous filament glass fibers	ACGIH	TWA	5	mg/m ³	(inhalable particulate matter), 1 f/cc (respirable fibers), A4, URT irr
	Diphenylmethane 4,4'-diisocyanate	ACGIH	TWA	0.005	ppm	Resp sens
	Diphenylmethane 4,4'-diisocyanate	OSHA	TWA	0.02	ppm	ceiling limit
	Diphenylmethane 4,4'-diisocyanate	OSHA	TWA	0.2	mg/m ³	ceiling limit
	Silicon dioxide, amorphous	OSHA	TWA	80	mg/m ³	/% SiO ₂ , 20 mppcf
Biological Limit Values	No biological limits allocated.					
Appropriate Engineering Controls	None required when used as intended. This substance is hazardous and should be used with a local exhaust ventilation system, drawing solid/dust away from workers' breathing zone. A flameproof exhaust ventilation system is required. If the engineering controls are not sufficient to maintain concentrations of particulates below the exposure standards, suitable respiratory protection must be worn.					
Respiratory Protection	None required when used as intended. If engineering controls are not effective in controlling airborne exposure then an approved respirator with a replaceable dust/particulate filter should be used. Refer to relevant regulations for further information concerning respiratory protective requirements.					
Eye Protection	None required when used as intended. Safety glasses with side shields, chemical goggles or full-face shield as appropriate should be used. Final choice of appropriate eye/face protection will vary according to individual circumstances. Eye protection devices should conform to relevant regulations.					
Hand Protection	Wear gloves of impervious material such as disposable gloves or nitrile disposable gloves included in the packaging. Final choice of appropriate gloves will vary according to individual circumstances. i.e. methods of handling or according to risk assessments undertaken. Occupational protective gloves should conform to relevant regulations.					
Body Protection	Suitable protective workwear, e.g. cotton overalls buttoned at neck and wrist is recommended. Chemical resistant apron is recommended where large quantities are handled.					
Other Information	No exposure standards have been established for the mixture. As with all chemicals, exposure should be kept to the lowest possible levels. Mineral oil, excluding metal working fluids (Pure, highly and severely refined) TWA: 5 mg/m ³ (Inhalable particulate matter) However, the recommended exposure standards for Particles (Insoluble or Poorly soluble) not otherwise specified, Inhalable Particles is: TWA: 10 mg/m ³ . However, the recommended exposure standards for Particles (Insoluble or Poorly soluble) not otherwise specified, Respirable Particles is: TWA: 3 mg/m ³ . Source: Adopted biological exposure determinants, American Conference of Industrial Hygienists (ACGIH). Oil mist, mineral TWA: 5 mg/m ³ However, the recommended exposure standards for Inert or Nuisance Dust, Total Dust is: TWA: 50 mppcf, 15 mg/m ³ . However, the recommended exposure standards for Inert or Nuisance Dust, Respirable Fraction is: TWA: 15 mppcf, 5 mg/m ³ . Source: OSHA Table Z-3 (29 CFR 1910.1000) TWA (Time Weighted Average): The average airborne concentration of a particular substance when calculated over a normal eight hour working day, for a five-day week.					

9. PHYSICAL AND CHEMICAL PROPERTIES

Form	Solid
Appearance	Knitted fabric coated with sticky resin.
Colour	White/off white
Odour	A unique, weak odour
Decomposition Temperature	Not available
Freezing Point	Not available
Boiling Point	Not available
Solubility in Water	Reacts in water
Specific Gravity	1.12 (77 °F) (25 °C)
pH	Not available
Vapour Pressure	Not available
Vapour Density (Air=1)	Not available
Evaporation Rate	Not available
Odour Threshold	Not available

SAFETY DATA SHEET – RAPP-IT PIPE REPAIR BANDAGE

Infosafe No™ LPXZ9

Version No. 2.0

Issue Date: 27/10/2020

ISSUED by PIPE REPAIR INTERNATIONAL

PAGE: 4 OF 6

Viscosity	Refer to Section 9: Kinematic Viscosity and Dynamic Viscosity
Partition Coefficient: n-octanol/water	Not available
Flash Point	> 392 °F (> 200 °C)
Flammability	Not flammable
Auto-Ignition Temperature	Not available
Explosion Limit - Upper	Not available
Explosion Limit - Lower	Not available
Explosion Properties	Not available
Oxidizing Properties	Not available
Kinematic Viscosity	Not available
Dynamic Viscosity	Not available

10. STABILITY AND REACTIVITY

Reactivity	Curing reaction occurs with water. Chemical resistance test results for the cured bandage for exposure for 1 month: 1. Exposure to ethanol, diesel, gasoline, pure water, toluene. No change in bandage. 2. Exposure to acetone, mineral spirits, xylene, MEK, sulfuric acid 30%. Some colour change. 3. Exposure to caustic soda 20% and caustic soda 50% - no colour change, slightly reduced hardness. Bandage maintained integrity. 4. Exposure to 50% nitric acid. Severe discoloration, slightly reduced hardness. Bandage maintained integrity. 5. Exposure to hydrochloric acid 30%. Severe discoloration, no softening of bandage.
Chemical Stability	Stable under normal conditions of storage and handling.
Conditions to Avoid	Avoid contact with incompatible materials and condition. Avoid: accumulation of electrostatic charges, heating, flames and hot surfaces. Avoid moisture or water before use. This will cause unwanted hardening.
Incompatible materials	Uncured bandage: Acids and bases, amines, alcohols and strong oxidizing agents.
Hazardous Decomposition Products	Under fire conditions this product may emit toxic and/or irritating fumes including carbon monoxide, carbon dioxide and oxides of nitrogen.
Possibility of hazardous reactions	Reacts with incompatible materials.
Hazardous Polymerization	Will not occur.

11. TOXICOLOGICAL INFORMATION

Toxicology Information	No toxicity data available for this material.
Ingestion	Ingestion unlikely due to form of product.
Inhalation	May cause respiratory irritation. Inhalation of product dust can cause irritation of the nose, throat and respiratory system. May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Skin	Causes skin irritation. Skin contact will cause redness, itching and swelling. Repeated exposure may cause skin dryness and cracking and may lead to dermatitis. May cause an allergic skin reaction.
Eye	Causes serious eye irritation. On eye contact this product will cause tearing, stinging, blurred vision, and redness.
Respiratory Sensitisation	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Skin Sensitisation	May cause an allergic skin reaction.
Germ cell mutagenicity	Not considered to be a mutagenic hazard.
Carcinogenicity	Suspected of causing cancer. Classified as a suspected human carcinogen. Glass filament, continuous, diphenylmethane 4,4'- diisocyanate, highly refined mineral oil and amorphous silica are listed as a Group 3: Not classifiable as to carcinogenicity to humans according to International Agency for Research on Cancer (IARC). Continuous filament glass fibers and mineral oil, excluding metal working fluids (pure, highly and severely refined) are listed as A4 – Not Classifiable as a Human Carcinogen according to American Conference of Industrial Hygienists (ACGIH).
Reproductive Toxicity	Not considered to be toxic to reproduction.
STOT-single exposure	May cause respiratory irritation.
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
Aspiration Hazard	Not expected to be an aspiration hazard.

SAFETY DATA SHEET – RAPP-IT PIPE REPAIR BANDAGE

Infosafe No™ LPXZ9

Version No. 2.0

Issue Date: 27/10/2020

ISSUED by PIPE REPAIR INTERNATIONAL

PAGE: 5 OF 6

12. ECOLOGICAL INFORMATION

Ecotoxicity	No ecological data available for this material.
Persistence and degradability	Not available
Mobility	Not available
Bioaccumulative Potential	Not available
Other Adverse Effects	Not available
Environmental Protection	Prevent this material entering waterways, drains and sewers.

13. DISPOSAL CONSIDERATIONS

Disposal Considerations	The disposal of the spilled or waste material must be done in accordance with applicable local and national regulations.
-------------------------	--

14. TRANSPORT INFORMATION

Transport Information	Not classified as Dangerous Goods by the criteria of the Department of Transport (DOT). Not classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air. Not classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.
UN Number (Air Transport, ICAO)	Not regulated
IATA/ICAO Proper Shipping Name	Not regulated
IATA/ICAO Hazard Class	Not regulated
IATA/ICAO Packing Group	Not regulated
IMDG UN No	Not regulated
IMDG Proper Shipping Name	Not regulated
IMDG Hazard Class	Not regulated
IMDG Pack. Group	Not regulated
IMDG Marine pollutant	No
DOT UN NO	Not regulated
DOT Proper Shipping Name	Not regulated
DOT Class	Not regulated
DOT Packing Group	Not regulated
DOT Identification (DOT)	Not applicable
DOT Special Requirements (Special)	Not applicable
DOT Exceptions (Exceptions)	Not applicable
DOT Symbols (SymbolS)	Not applicable
DOT Non-Bulk Requirements (NON_BULK)	Not applicable
DOT Bulk Requirements (BULK)	Not applicable
DOT Max. Passgr. Air/Rail. (MAXAIR)	Not applicable
DOT Max. Cargo Only Air/Rail. (MAXCARGO)	Not applicable
DOT Stowage (Stowage)	Not applicable
DOT Other Requirements (OTHER)	Not applicable
Transport in Bulk	Not available
Special Precautions for User	Not available

SAFETY DATA SHEET – RAPP-IT PIPE REPAIR BANDAGE

Infosafe No™ LPXZ9

Version No. 2.0

Issue Date: 27/10/2020

ISSUED by PIPE REPAIR INTERNATIONAL

PAGE: 6 OF 6

15. REGULATORY INFORMATION

California Proposition 65	Not Listed
SARA Section 302	Not Listed
SARA (311,312) Hazard Class	Skin Corrosion/Irritation: Category 2 Eye Damage/Irritation: Category 2 Sensitization - Respiratory: Category 1 Sensitization - Skin: Category 1 Carcinogenicity: Category 2 STOT Single Exposure: Category 3 (respiratory tract irritation) STOT Repeated Exposure: Category 2
SARA (313) Chemicals	Listed
USA (TSCA)	Listed
Reportable Quantity	5000 lbs
Other Information	Canada Canada (DSL/NDSL): Listed Canadian NPRI: Listed CEPA Toxic substances: Not listed

16. OTHER INFORMATION

Date of preparation or last revision of SDS	SDS Reviewed: October 2020 Supersedes: September 2019
References	ANSI Z400.1/Z129.1-2010. American National Standard for Hazardous Workplace Chemicals – Hazard Evaluation and Safety Data Sheet and Precautionary Labeling Preparation. Adopted biological exposure determinants, American Conference of Industrial Hygienists (ACGIH). OSHA Table Z-1 Limits for Air Contaminants (June 30, 1993)(29 CFR 1910.1000)(1971 Permissible Exposure Limits (PELs)). OSHA Table Z-3 (29 CFR 1910.1000).
Contact Person/Point	Tel: +61 7 3262 3755

...END OF SDS...

© Copyright Chemical Safety International Pty Ltd

Copyright in the source code of the HTML, PDF, XML, XFO and any other electronic files rendered by an Infosafe system for Infosafe SDS displayed is the intellectual property of Chemical Safety International Pty Ltd.

Copyright in the layout, presentation and appearance of each Infosafe SDS displayed is the intellectual property of Chemical Safety International Pty Ltd.

The compilation of SDS's displayed is the intellectual property of Chemical Safety International Pty Ltd.

Copying of any SDS displayed is permitted for personal use only and otherwise is not permitted. In particular the SDS's displayed cannot be copied for the purpose of sale or licence or for inclusion as part of a collection of SDS without the express written consent of Chemical Safety International Pty Ltd.



SAFETY DATA SHEET – RAPP-IT STEEL PUTTY 90MM

Infosafe No™ LQ5PY

Version No. 2.0

Issue Date: 08/05/2019


ISSUED by PIPE REPAIR INTERNATIONAL

PAGE: 1 OF 6

1. IDENTIFICATION

GHS Product Identifier	RAPP-IT STEEL PUTTY 90MM
Company Name	PIPE REPAIR INTERNATIONAL
Address	12/14 Argyle Street, Albion, Queensland 4010 Australia
Telephone/Fax Number	Tel: +61 7 3262 3755 Fax: +61 7 3262 3255
Emergency Phone Number	INFOTRAC 24/7 Emergency response contact phone numbers 1-800-535-5053 (free call from USA and Canada) 1-352-323-3500 (outside USA and Canada) 01-800-681-1530 (Mexico - local charges apply)
Recommended use of the chemical and restrictions on use	Adhesives, Sealants.
Manufacturer Information	MARINE & INDUSTRIAL MARKETING 12/14 Argyle Street, Albion, Queensland 4010 Australia

2. HAZARD IDENTIFICATION

GHS classification of the substance or mixture	This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200). Skin Corrosion/Irritation: Category 2 Eye Damage/Irritation: Category 2 Sensitization - Skin: Category 1
Signal Word(s)	WARNING
Hazard Statement(s)	Causes skin irritation. Causes serious eye irritation. May cause an allergic skin reaction.
Pictogram(s)	Exclamation mark 
Precautionary Statement – Prevention	Avoid breathing dust. Wash hands and contaminated skin thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection.
Precautionary Statement – Response	IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention. Take off immediately all contaminated clothing and wash it before reuse. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
Precautionary Statement – Disposal	Dispose of contents/container to an approved waste disposal plant.
Other Information	No exposure to free respirable silica is anticipated during normal use of this product. During cutting or demolition operations crystalline silica may become available for breathing. HMIS rating: Health Hazards: 2 Flammability: 0 Physical hazard: 0 Personal Protective Equipment: X

SAFETY DATA SHEET – RAPP-IT STEEL PUTTY 90MM

Infosafe No™ LQ5PY

Version No. 2.0

Issue Date: 08/05/2019

ISSUED by PIPE REPAIR INTERNATIONAL

PAGE: 2 OF 6

3. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients	Name	CAS	EINECS	Proportion
	Talc	14807-96-6	238-877-9	30-60 %
	Glass, oxide, chemicals	65997-17-3	266-046-0	10-30 %
	Epichlorohydrin, bisphenol A resin	25068-38-6	500-033-5	10-<25 %
	Quartz [Silica Crystalline]	14808-60-7	238-878-4	0.1-1 %
	Ingredients determined not to be hazardous			Balance

Other Information Fibreglass type: Continuous filament glass fibers (E-type).
Quartz [Silica Crystalline]: Non-respirable
This product contains non-respirable crystalline silica and talc, which are embedded in an impervious polymer matrix. No exposure to free respirable silica is anticipated during normal use of this product.

4. FIRST AID MEASURES

Inhalation	If inhaled, remove affected person from contaminated area. Keep at rest until recovered. If symptoms develop and/or persist seek medical attention.
Ingestion	Do not induce vomiting. Wash out mouth thoroughly with water. Seek immediate medical attention.
Skin	Remove all contaminated clothing immediately. Wash affected area thoroughly with soap and water. Wash contaminated clothing before reuse or discard. Seek medical attention.
Eye contact	If in eyes, hold eyelids apart and flush the eyes continuously with running water. Remove contact lenses. Continue flushing for several minutes until all contaminants are washed out completely. Seek medical attention.
First Aid Facilities	Eyewash, safety shower and normal washroom facilities.
Advice to Doctor	Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Most important symptoms/ effects, acute and delayed	Potential acute health effects Skin contact: Causes skin irritation. May cause an allergic skin reaction. Eye contact: Causes eye irritation. Over-exposure signs/symptoms Skin contact: Adverse symptoms may include the following: irritation, redness. Eye contact: Adverse symptoms may include the following: pain or irritation, watering, redness.
Other Information	For advice in an emergency, contact a Poisons Information Centre or a doctor at once.

5. FIRE FIGHTING MEASURES

Suitable Extinguishing Media	Use appropriate fire extinguisher for surrounding environment.
Hazards from Combustion Products	Under fire conditions this product may emit toxic and/or irritating fumes, smoke and gases including oxides of sulphur, halogenated compounds, metal oxides, carbon monoxide, carbon dioxide and oxides of nitrogen.
Specific Hazards arising from the Chemical	This product is non combustible. However heating can cause expansion or decomposition leading to violent rupture of containers.
Decomposition Temp.	>302°F (>150°C)
Precautions in connection with Fire	Isolate the area. No action shall be taken involving any personal risk or without suitable training. Fire fighters should wear full protective clothing and self-contained breathing apparatus (SCBA) operated in positive pressure mode. Fight fire from safe location.
Other Information	NFPA rating: Health Hazards: 2 Flammability: 0 Instability: 0

6. ACCIDENTAL RELEASE MEASURES

Emergency Procedures	No action shall be taken involving any personal risk or without suitable training. Increase ventilation. Evacuate all unprotected personnel. Do not touch or walk through spilled material. Wear sufficient respiratory protection and full protective clothing to prevent exposure. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Avoid exposure to spillage by sweeping up material avoiding dust generation - dampen spilled material with water if suitable to avoid airborne dust, OR where possible use dustless methods such as vacuum to collect the material; then transfer material in to suitable labelled containers for subsequent recycling or disposal. Keep containers tightly closed. Wash surfaces well with soap and water. Dispose of waste according to the applicable local and national regulations. If contamination of sewers or waterways occurs inform the local water and waste management authorities in accordance with local regulations. Recommended Materials - Filter type: High-efficiency particulate air (HEPA) filter
----------------------	---

SAFETY DATA SHEET – RAPP-IT STEEL PUTTY 90MM

Infosafe No™ LQ5PY

Version No. 2.0

Issue Date: 08/05/2019

ISSUED by PIPE REPAIR INTERNATIONAL

PAGE: 3 OF 6

7. HANDLING AND STORAGE

Precautions for Safe Handling Avoid inhalation of dust, and skin or eye contact. Do not ingest. Use only in a well ventilated area. Keep containers sealed when not in use. Maintain high standards of personal hygiene i.e. washing hands prior to eating, drinking, smoking or using toilet facilities. Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Remove contaminated clothing and protective equipment before entering eating areas. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Empty containers may contain hazardous residues. Do not re-use container.

Conditions for Safe Storage including any Incompatibilities Store in a cool, dry, well-ventilated area, out of direct sunlight and moisture. Keep only in original container. Do not store in unlabelled containers. Keep containers tightly closed. Store away from incompatible materials. Keep away from food, drink and animal feeding stuffs. In order to prevent spillages, always ensure that these containers are stored and transported in upright position. Ensure that storage conditions comply with applicable local and national regulations. Use appropriate containment (of product and fire fighting water) to avoid environmental contamination.

Storage Temperatures Store below 95°F (35°C).

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupation Exposure Limit Values	Substance	Regulations	Exposure Duration	Exposure Limit	Units	Notes
	Quartz [Silica Crystalline]	ACGIH	TWA	0.025	mg/m3	(respirable fraction), A2, Pulm fibrosis; lung cancer
	Continuous filament glass fibers	ACGIH	TWA	5	mg/m3	(inhalable particulate matter), 1 f/cc (respirable fibers), A4, URT irr
	Talc	ACGIH	TWA	2	mg/m3	(respirable), A4, Pulm fibrosis; pulm func (containing no asbestos fibres)
	Quartz (Respirable)	OSHA	TWA	0.05	mg/m3	10 mg/m ³ /(%SiO ₂ +2), 250/(%SiO ₂ +5) mppcf
	Quartz (Total Dust)	OSHA	TWA	30	mg/m3	/(%SiO ₂ +2)
	Talc (not containing asbestos)	OSHA	TWA	-	mg/m3	20 mppcf
Biological Limit Values	No biological limits allocated.					
Appropriate Engineering Controls	Use with good general ventilation. However, if dust formation occurs after completion of application and/or during mechanical machining for removal or refinishing (for example, sawing, drilling, grinding etc.), occupational regulations have to be considered. This substance is hazardous and should be used with a local exhaust ventilation system, drawing dust/vapor away from workers' breathing zone. If the engineering controls are not sufficient to maintain concentrations of particulates below the exposure standards, suitable respiratory protection must be worn.					
Respiratory Protection	If engineering controls are not effective in controlling airborne exposure then an approved respirator with a replaceable dust/vapor filter should be used.					
Eye Protection	Safety glasses with side shields, chemical goggles or full-face shield as appropriate should be used. Final choice of appropriate eye/face protection will vary according to individual circumstances. Eye protection devices should conform to relevant regulations.					
Hand Protection	Wear gloves of impervious material. Final choice of appropriate gloves will vary according to individual circumstances i.e. methods of handling or according to risk assessments undertaken. Occupational protective gloves should conform to relevant regulations.					
Body Protection	Suitable protective workwear, e.g. cotton overalls buttoned at neck and wrist is recommended. Chemical resistant apron is recommended where large quantities are handled.					

9. PHYSICAL AND CHEMICAL PROPERTIES

Form	Solid
Appearance	Grey, Black [Dark] solid
Color	Grey, Black [Dark]
Odor	Sulfurous. Pungent. [Strong]
Decomposition Temperature	>302°F (>150°C)
Melting Point	Not available
Boiling Point	Not available
Solubility in Water	Insoluble in the following materials: cold water and hot water.
Solubility in Organic Solvents	Partially soluble in the following materials: methanol, diethyl ether, n-octanol and acetone.
Specific Gravity	2.25

SAFETY DATA SHEET – RAPP-IT STEEL PUTTY 90MM

Infosafe No™ LQ5PY

Version No. 2.0

Issue Date: 08/05/2019

ISSUED by PIPE REPAIR INTERNATIONAL

PAGE: 4 OF 6

pH	Not applicable
Vapor Pressure	Not available
Vapor Density (Air=1)	Not available
Evaporation Rate	Not applicable
Odor Threshold	Not available
Viscosity	Refer to Section 9: Kinematic Viscosity and Dynamic Viscosity
Partition Coefficient: n-octanol/water	Not available
Flash Point	Not applicable Does not sustain combustion (Closed Cup)
Flammability	Not flammable
Auto-Ignition Temperature	Not available
Explosion Limit - Upper	Not applicable
Explosion Limit - Lower	Not available
Kinematic Viscosity	Not applicable
Dynamic Viscosity	Not applicable

10. STABILITY AND REACTIVITY

Reactivity	Refer to Section 10: Possibility of hazardous reactions
Chemical Stability	Stable under normal conditions of storage and handling.
Conditions to Avoid	Extremes of temperature and direct sunlight.
Incompatible Materials	Not available
Hazardous Decomposition Products	Thermal decomposition may result in the release of toxic and/or irritating fumes including: oxides of sulphur, halogenated compounds, metal oxides, carbon monoxide and carbon dioxide.
Possibility of hazardous reactions	Reacts with incompatible materials. Under normal conditions of storage and use, hazardous reactions will not occur.
Hazardous Polymerization	Not available

11. TOXICOLOGICAL INFORMATION

Toxicology Information	Toxicity data for material given below.
Ingestion	Ingestion of this product may irritate the gastric tract causing nausea and vomiting.
Inhalation	Inhalation of dusts may irritate the respiratory system.
Skin	Causes skin irritation. Skin contact will cause redness, itching and swelling. Repeated exposure may cause skin dryness and cracking and may lead to dermatitis. May cause an allergic skin reaction. Epichlorohydrin, bisphenol A resin Result: Moderately irritating (rabbit, 500 µL/24h) Result: Severe skin irritation (rabbit, 2 mg/24h)
Eye	Causes serious eye irritation. On eye contact this product will cause tearing, stinging, blurred vision, and redness. Epichlorohydrin, bisphenol A resin Result: Mildly irritating (rabbit, 100 mg/24h)
Respiratory Sensitisation	Not expected to be a respiratory sensitiser.
Skin Sensitisation	May cause an allergic skin reaction.
Germ cell mutagenicity	Not considered to be a mutagenic hazard.
Carcinogenicity	Not considered to be a carcinogenic hazard. This product contains crystalline silica. Crystalline Silica (respirable size $\leq 18 \mu\text{m}$) has been classified by the International Agency for Research on Cancer (IARC) as Carcinogenic to Humans (Group 1). Talc not containing asbestos or asbestiform fibres is listed as a Group 3: Not classifiable as to carcinogenicity to humans according to International Agency for Research on Cancer (IARC). Glass filament, continuous is listed as a Group 3: Not classifiable as to carcinogenicity to humans according to International Agency for Research on Cancer (IARC). Silica, crystalline is listed as A2 – Suspected Human Carcinogen according to American Conference of Industrial Hygienists (ACGIH). Continuous filament glass fibers is listed as A4 – Not Classifiable as a Human Carcinogen according to American Conference of Industrial Hygienists (ACGIH). Talc containing no asbestos fibers is listed as A4 – Not Classifiable as a Human Carcinogen according to American Conference of Industrial Hygienists (ACGIH). Silica, Crystalline (Respirable Size) is listed under 'Known To Be Human Carcinogens' in the Report on Carcinogens, according to the National Toxicology Program (NTP).

SAFETY DATA SHEET – RAPP-IT STEEL PUTTY 90MM

Infosafe No™ LQ5PY

Version No. 2.0

Issue Date: 08/05/2019

ISSUED by PIPE REPAIR INTERNATIONAL

PAGE: 5 OF 6

This product contains talc in a polymer matrix. Sanding the cured product may release particles containing talc with the polymer and other components of the matrix into the air. The talc contains less than 1% crystalline silica. Appropriate evaluations of the use of the product should be performed to determine if exposure to talc occurs due to handling and use.

Reproductive Toxicity	Not considered to be toxic to reproduction.
STOT-single Exposure	Not expected to cause toxicity to a specific target organ.
STOT-repeated Exposure	Not expected to cause toxicity to a specific target organ.
Aspiration Hazard	Not expected to be an aspiration hazard.

12. ECOLOGICAL INFORMATION

Ecotoxicity	Harmful to aquatic life with long lasting effects.
Persistence and Degradability	Not available
Mobility	Insoluble in water.
Bioaccumulative Potential	Product: Not available Epichlorohydrin, bisphenol A resin: Low bioaccumulation potential. Bioconcentration Factor (BCF): 31 logPow: 2.64-3.78
Other Adverse Effects	No known significant effects or critical hazards.
Environmental Protection	Prevent this material entering waterways, drains and sewers.

13. DISPOSAL CONSIDERATIONS

Disposal Considerations	Dispose of waste according to applicable local and national regulations. Do not allow into drains or watercourses or dispose of where ground or surface waters may be affected. Wastes including emptied containers are controlled wastes and should be disposed of in accordance with all applicable local and national regulations. Dispose of contents/ container to a licensed waste contractor. Contaminated packaging should be emptied as far as possible; then it can be passed on for recycling after being thoroughly cleaned. Empty containers may contain hazardous residues. Incineration or landfill should only be considered when recycling is not feasible.
-------------------------	--

14. TRANSPORT INFORMATION

Transport Information	Not classified as Dangerous Goods by the criteria of the Department of Transport (DOT). Not classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air. Not classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.
UN Number (Air Transport, ICAO)	Not regulated
IATA/ICAO Proper Shipping Name	Not regulated
IATA/ICAO Hazard Class	Not regulated
IATA/ICAO Packing Group	Not regulated
IMDG UN No	Not regulated
IMDG Proper Shipping Name	Not regulated
IMDG Hazard Class	Not regulated
IMDG Pack. Group	Not regulated
IMDG Marine pollutant	No
DOT UN NO	Not regulated
DOT Proper Shipping Name	Not regulated
DOT Class	Not regulated
DOT Packing Group	Not regulated
DOT Identification (DOT)	Not applicable
DOT Special Requirements (Special)	Not applicable
DOT Exceptions (Exceptions)	Not applicable
DOT Symbols (SymbolS)	Not applicable

SAFETY DATA SHEET – RAPP-IT STEEL PUTTY 90MM

Infosafe No™ LQ5PY Version No. 2.0 Issue Date: 08/05/2019 ISSUED by PIPE REPAIR INTERNATIONAL PAGE: 6 OF 6

DOT Non-Bulk Requirements (NON_BULK)	Not applicable
DOT Bulk Requirements (BULK)	Not applicable
DOT Max. Passgr. Air/Rail. (MAXAIR)	Not applicable
DOT Max. Cargo Only Air/Rail. (MAXCARGO)	Not applicable
DOT Stowage (Stowage)	Not applicable
DOT Other Requirements (OTHER)	Not applicable
Transport in Bulk	Not available
Special Precautions for User	Closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

15. REGULATORY INFORMATION

TSCA Inventory Status	Silicones and siloxanes, dimethyl-, reaction product with silica TSCA 8(a) PAIR: Listed
California Proposition 65	This product contains chemical(s) known to the state of California to cause cancer and/or to cause birth defects or other reproductive harm. Silica, crystalline (airborne particles of respirable size) - Type of Toxicity: Cancer Carbon black (airborne, unbound particles of respirable size) - Type of Toxicity: Cancer
SARA Section 302	Not Listed
SARA (311,312) Hazard Class	Skin Corrosion/Irritation: Category 2 Eye Damage/Irritation: Category 2 Sensitization - Skin: Category 1
SARA (313) Chemicals	Not Listed
USA (TSCA)	All components of this product are listed on the Inventory or exempted.
Reportable Quantity	No reportable quantity
Other Information	Canada Canada (DSL/NDSL): All components are listed or exempted. Canadian NPRI: Not listed CEPA Toxic substances: Not listed

16. OTHER INFORMATION

Date of preparation or last revision of SDS	SDS Created: May 2019
References	ANSI Z400.1/Z129.1-2010. American National Standard for Hazardous Workplace Chemicals – Hazard Evaluation and Safety Data Sheet and Precautionary Labeling Preparation. Adopted biological exposure determinants, American Conference of Industrial Hygienists (ACGIH). OSHA Table Z-1 Limits for Air Contaminants (June 30, 1993)(29 CFR 1910.1000)(1971 Permissible Exposure Limits (PELs)). OSHA Table Z-3 (29 CFR 1910.1000).
Contact Person/Point	Tel: +61 7 3262 3755

...END OF SDS...

© Copyright Chemical Safety International Pty Ltd

Copyright in the source code of the HTML, PDF, XML, XFO and any other electronic files rendered by an Infosafe system for Infosafe SDS displayed is the intellectual property of Chemical Safety International Pty Ltd.

Copyright in the layout, presentation and appearance of each Infosafe SDS displayed is the intellectual property of Chemical Safety International Pty Ltd.

The compilation of SDS's displayed is the intellectual property of Chemical Safety International Pty Ltd.

Copying of any SDS displayed is permitted for personal use only and otherwise is not permitted. In particular the SDS's displayed cannot be copied for the purpose of sale or licence or for inclusion as part of a collection of SDS without the express written consent of Chemical Safety International Pty Ltd.